


Black & Decker.

OWNER'S MANUAL





1/4" DRILL #1015
3/8" DRILL #1161

VARIABLE SPEED SWITCH

0 to 2250 R.P.M. Capacity: 1/4" holes in steel; 1/2" in hardwood. 115 Volts A.C. 2 Amps. 1/7 H.P.

VARIABLE SPEED SWITCH

0 to 1000 R.P.M. Capacity: 3/8" holes in steel; 3/4" in hardwood. 115 Volts A.C. 2.2. Amps. 1/7 H.P.



SAFETY RULES FOR POWER TOOLS

- 1. KNOW YOUR POWER TOOL Read owner's manual carefully. Learn its applications and limitations as well as the specific potential hazards peculiar to this tool.
- 2. **GROUND ALL TOOLS UNLESS DOUBLE-INSULATED.** If tool is equipped with three-prong plug, it should be plugged into a three-hole electrical receptacle. If adapter is used to accommodate two-prong receptacle, the adapter wire must be attached to a **known ground.** Never remove third prong.
- 3. KEEP GUARDS IN PLACE and in working order.
- 4. KEEP WORK AREA CLEAN. Cluttered areas and benches invite accidents.
- 5. AVOID DANGEROUS ENVIRONMENT. Don't use power tool in damp or wet locations. And keep work area well lit.
- 6. KEEP CHILDREN AWAY. All visitors should be kept safe distance from work area.
- 7. **STORE IDLE TOOLS.** When not in use, tools should be stored in dry, high or locked-up place out of reach of children.
- 8. **DON'T FORCE TOOL.** It will do the job better and safer at the rate for which it was designed.
- 9. USE RIGHT TOOL. Don't force small tool or attachment to do the job of a heavy duty tool.
- 10. WEAR PROPER APPAREL. No loose clothing or jewelry to get caught in moving parts. Rubber gloves and footwear are recommended when working outdoors.
- 11. **USE SAFETY GLASSES** with most tools. Also face or dust mask if cutting operation is dusty.
- 12. **DON'T ABUSE CORD.** Never carry tool by cord or yank it to disconnect from receptacle. Keep cord from heat, oil and sharp edges.
- 13. **SECURE WORK.** Use clamps or a vise to hold work. It's safer than using your hand and it frees both hands to operate tool.
- 14. DON'T OVERREACH. Keep proper footing and balance at all times.
- 15. MAINTAIN TOOLS WITH CARE. Keep tools sharp at all times, and clean for best and safest performance. Follow instructions for lubricating and changing accessories.
- 16. **DISCONNECT TOOLS.** When not in use, before servicing; when changing accessories such as blades, bits, cutters, etc.
- 17. **REMOVE ADJUSTING KEYS AND WRENCHES.** Form habit of checking to see that keys and adjusting wrenches are removed from tool before turning it on.
- 18. AVOID ACCIDENTAL STARTING. Don't carry plugged-in tool with finger on switch.

GROUNDING

EVERY ELECTRIC TOOL SHOULD BE GROUNDED while in use to protect the operator against shock. This unit is equipped with approved 3-conductor cord and 3-blade grounding type attachment plug to be used with the proper grounding type receptacle. The green colored conductor in the cord is the grounding wire. Never connect the green wire to a "live" terminal. If your unit requires less than 150 volts, it has a plug that looks like fig. "A". A special grounding adapter (Fig. "B") is available from your dealer to permit using 2-wire receptacle until the correct receptacle is properly installed. The green grounding wire extending from the side of the adapter must be connected to a PERMANENT GROUND such as a properly grounded outlet box. If the unit requires from 150 to 250 volts it has a plug like Figure "C". No adapter is available and it should be used in the proper standard matching 3-wire grounding receptacle.









SWITCH

The Variable Speed Trigger Switch permits "FREE HAND" speed control — the farther the trigger is depressed, the higher the R.P.M. of the Drill. A Switch Locking Button permits locking the trigger in the full "ON" position for continuous operation, or when using the Drill in a Vertical Stand. To lock the trigger "ON," depress trigger fully and push in locking button, then gently release trigger. To release locking mechanism, depress trigger fully, then release it.

NOTE: Use lower speeds for STARTING HOLES WITHOUT A CENTER PUNCH, DRILLING IN METAL OR PLASTICS, DRIVING SCREWS, DRILLING CERAMICS, OR MIXING PAINT. Higher speeds are better for DRILLING WOOD AND COMPOSITION BOARDS, AND FOR USING ABRASIVE AND POLISHING ACCESSORIES.

CABLE


The cable is the life-line of your tool. Keep it clean by wiping occasionally to remove any grease or oil. Don't let it become kinked. Avoid dragging it across sharp surfaces. Do not lift the tool by the cable.

When using the tool at a considerable distance from power source, a properly grounded extension cable of adequate size must be used to prevent loss of power and over-heating. Use table at right for 115 Volt tools. For 220 tools, use wire size of $\frac{1}{2}$ the contemplated cable length.

Ext. cable length in feet25 50 75 100 150 200

Required wire size (A.W.G.) in cable .. 18 18 18 18 16 16

DRILLING



INSERTING DRILL BIT IN CHUCK

Turn collar to open chuck jaws. Place bit in chuck so that end rests on chuck bottom. Tighten chuck collar by hand. Place chuck key in each of the three holes, and tighten in clockwise direction. It's important to tighten chuck with all three holes. This is a safety feature that prevents bit slippage and motor damage. To release bit, turn chuck key counterclockwise in just one hole, then loosen chuck by hand.

STARTING THE HOLE — WITH A VARIABLE SPEED DRILL, using a slow speed will enable you to start the hole accurately in most cases without the need for center punching.

CARE IN DRILLING

Twist drills are brittle and will break if enough bending stress it applied. To avoid stress on the drill bit, try extending your index finger along the side of the drill-housing with your middle finger on the trigger. Remember—guide, the tool, don't force it! Should the tool become overheated, run it with no load. Because of the drill's construction, it will cool faster running than by stopping it.

DRILLING IN METAL

Use a cutting lubricant when drilling metals. The exceptions are iron and brass which should be drilled dry. The cutting lubricants that work best are sulphurized cutting oil or lard oil; bacon grease will also serve the purpose. Aluminum is best drilled with turpentine or kerosene.

DRILLING IN WOOD

Holes in wood can be made with the same twist drills used for metal. These bits may overheat unless pulled out frequently to clear chips from the flutes. Work that is apt to splinter should be backed up with a block of wood. Let up on the pressure just before the tip cuts through, this will give a good clean hole.

TO REMOVE THE CHUCK — Place the chuck key in one of the holes in the chuck. Strike the key sharply with a piece of wood in the direction that the chuck normally rotates. This will loosen the chuck so that it can be unscrewed by hand.

GUARANTEE

Black & Decker will correct, without charge, any defect AT ANY TIME which, upon examination at one of our Factory Service Branches, Authorized Service Stations, or Factories, is found to be due to faulty material or workmanship. The guarantee does not apply in cases of misuse or careless handling or where repairs or replacements have been made or attempted by others. Any transportation charges for delivering the unit for examination must be prepaid.

IF THE TOOL WON'T RUN

First, check the outlet by plugging in another tool or lamp. If these don't work, check the service panel for blown fuses. If current is present, check plugs and sockets for tight fits. If there is something wrong with the tool, don't attempt any major repair on your own. Take it or send it to the nearest Service location shown below for repair. A free parts diagram of your B&D tool is available by writing the Black & Decker Factory Service Center nearest you.

FACTORY SALES & SERVICE BRANCHES



	Area Code	Telephone No.	Area	Telephone
	ALABAMA: Birmingham 35233, 1717 Third Ave., South205	324-6691	Code	Ño.
	ARIZONA: Phoenix 85004, 537 E. McDowell Rd	AI 8-1332	NEW MEXICO: Albuquerque 87110, 4700 Loinas Blvd, N.E. 505	265-6401
	ARKANSAS: Little Rock 72201, 519 West Seventh Street. 501	FR 2-3040	NEW YORK: Buffalo 14209, 881 W. Delevan Ave	TT 4-6220 SY 2-2700
	CALIFORNIA: Anaheim 92802, 1235 So Fucild Ave. 714	772-4050		WA 9-6450
	Los Angeles 90007, 2432 S. Broadway 213 Oakland 94506, 1107 E. 14th St. 415	RI 9-0371	New York 11377, 56-15 Queens Blvd. (Woodside). 212 Rochester 14620, 476 Clinton Ave., S	DE 5-1042
		TE 4-5944 444-3188	Syracuse 13224, 2140 Erie Blvd., E	454-3814 446-3086
		AT 1-3331	NORTH CAROLINA: Charlotte 28206 1710 N Graham St. 704	FR 5-3721
	San Francisco 94080, 1139 Airport Blvd. 415 Santa Clara 95050, 2291 The Alameda 408	871-7278	rayetteville 2830b, P.O. Box 4305 Highway 301 C 010	425-1181
	COLORADO: Denver 80204, 675 Kalamath St303	241-9162 222-0621	Greensboro 27403, 1008 W. Lee Street	275-0906 421-2275
	CONNECTICUT: Hartford 06114, 131 Meadow Street 203	249-6241		OL 1-4243
	LURIDA: Jacksonville 32208 5224 Poort Street	356-2951	Columbus 43202, 3293 N. High Street 614 Dayton 45420, 617 Watervliet St. 513	268-5797
	Miami 33142, 2075 N.W. 54th Street 305 Orlando 32806, 940 So. Orange Ave. 305	NE 3-9839 423-1651	301011 44139, 0223 Cocnran Road . 916	252-1821 CH 8-5330
	Tampa 33609, 3041 J. F. Kennedy Blvd	839-5323	Toledo 43000, 2029 W. Central Ave	475-6771
	GEORGIA: Atlanta 30313, 316 Techwood Drive, N.W404	JA 4-0431	OKLAHOMA: Oklahoma City 73106, 1318 Linwood Blvd. 405 Tulsa 74145, 3120 South Sheridan Road	CE 2-7515 622-5666
	HAWAII: Honolulu 96813, 675 Auahi Street808	569-374	OREGON: Portland 97209, 1640 N.W. Johnson Street 503	CA 8-8631
	ILLINOIS: Chicago 60607, 1100 W. Jackson Blvd 312 Chicago 60646, Lincolnwood, 6710 N. Crawford Ave 312 Chicago 60643, Brussland 110 N. Crawford Ave	TA 9-3500 OR 3-0923	PENNSYLVANIA: Harrisburg 17112, 6070 Allentown Blvd. 717	KI 5-0651
	Circago 00043, Deverio Hills, 10/08 S. Wastern Ava 212	BE 3-6832	Lancaster 1/004. /15 Fountain Ava 717	393-5831
	Rock Island 61201, 725 30th Street	788-1744	Philadelphia 19103, 333 No. 20th Street	LO 4-5520
	INDIANA: Evansville 47708, 931 Bond Street	425-4269	RHODE ISLAND: E. Providence 02914, 2777 Pawtucket Ave 401	362-2700 434-1655
	IOWA: Des Moines 50312, 2811 Ingersoll Ave515	632-5569 CH 4-7257	SOUTH CAROLINA: Greenville 29601, 407 Pendleton St803	232-3038
	KANSAS: Wichita 67214, 203 N. Mathewson Street. 316	FO 3-6571	TENNESSEE: Knoxville 37917 1123 North Central St 515	546-2481
	KENTUCKY: Louisville 40209, 4407 Park Blvd 502	366-1495	Mempins 3010b, 921 South Third St 901	WH 2-3244
	EUUISIANA: New Orleans 70112, 2010 Poydras Street 504	522-2544	Nashville 37203, 601 Eighth Ave., S	254-1061
	MARYLAND: Baltimore 21211 203 West 28th Street 201	HO 7-7411	TEXAS: Amarillo 79106, 3008 West 6th Ave. 806 Dallas 75207, 1808 N. Industrial Blvd. 214	DR 3-1531 RI 1-6401
	Baltimore 21205, 4712 Erdman Ave	485-5550 779-3808		ED 6.0175
	MASSACHUSETTS: Boston 02135, 12 Market St. (Brighton) .617	ST 2-6264	Houston 77003, 105 Sampson Street	CA 8-7521 LE 4-4611
	MICHIGAN: Detroit 48219, 18133 W McNicholae Pd 213	534-8880		HU 6-7056
	Detroit 48234, 11360 East Seven Mile Road 313 Grand Rapids 49509, 3662 Clyde Park Ave., S.W616	527-5010	VIRGINIA: Falls Church 22046, 129 Annandale Poad 703	533-1147
	MINNESOTA: Minneapolis 55408, 2815 Nicollet Ave	534-7708	NOПОК 2351/. 33/ W. 21st Street 702	625-6888
	MISSOURI: Kansas City 64108, 2705 McGee Trafficway 916	TA 3-5283 HA 1-1493	Richmond 23222, 1424 Chamberlayne Ave	649-9245
	3t. Louis 63110, 615 S. Vandeventer Ave314	JE 3-2210	WASHINGTON: Seattle 98109, 434 Eighth Ave., N 206 Spokane 99202, 3025A E. Mission Ave 509	MA 3-6442 KE 4-7188
	NEBRASKA: Omaha 68102, 2218 Leavenworth Street 402	345-2330	WEST VIRGINIA: Charleston 25312, 1638 Sixth Ave304	343-0289
	NEW JERSEY: Newark 07104, 868 Broadway201	HU 3-1076	WISCONSIN: Milwaukee 53213, 6301 Blue Mound Road414	GR 6-7800
BLACK & DECKER MEG. CO. Limited Consd.				
	CALGARY, ALBERTA		DON MILLS (Toronto) 2 Valleybrook Driv	/e
			QUEBEC CITY, P. Q	
	HAMILTON, ONTARIO			
			WINDSOR ONTARIO	
	MONTREAL WEST, P. Q	anald Drive	WINNIPEG 10, MANITOBA955 Portage Av	e.
	Av	enue, west		

ALABAMA: Montgomery ALASKA: Anchorage, Fairbanks ARIZONA: Tucson CALIFORNIA: Fresno, Stockton

CONNECTICUT: New Haven DELAWARE: Wilmington FLORIDA: Pensacola IDAHO: Boise, Lewiston

AUTHORIZED SERVICE STATIONS MAINE: Westbrook MISSISSIPPI: Jackson

NEVADA: Reno NEW YORK: Schnectady

OHIO: Youngstown
PENNSYLVANIA: Allentown,
Erie
SOUTH CAROLINA: Charleston
SOUTH DAKOTA: Rapid City

TEXAS: Corpus Christi,
El Paso
VIRGINIA: Roanoke
WASHINGTON: Yakima
WEST VIRGINIA: Wheeling

THE BLACK & DECKER MFG. CO., TOWSON, MD. 21204, U.S.A.

Form No. 97811 AL

Printed in U.S.A.